

BOTTTEGA

ceramica e stife

CERSAIE 2022

BLONDE

feelwood

GRES PORCELLANATO
PORCELAIN TILE

Sviluppo grafico - Different patterns



24X150
9.5"x59"



HONED

20X120 Rettificato
8"x48" RECTIFIED



7,5X40,7 CHEVRON
2.9"x16" CHEVRON





COGNAC



SMOKE

| |  |  |  |  |  |
|------------------------------|---|---|---|---|---|
| | 24x150 9.5"x59" | 20x120 rett. 8"x48" rect. | 7,5x40,7 2.9"x16" | Battiscopa 6x150 3"x59" | Battiscopa 6x120 rett. 3"x48" rect. |
| Finish | Natural | Oiled | Natural | Natural | Oiled |
| BLONDE | B71001 | B71007 | B71013 | B71016 | B71019 |
| COGNAC | B71002 | B71008 | B71014 | B71017 | B71020 |
| SMOKE | B71003 | B71009 | B71015 | B71018 | B71021 |
| Spessore Thickness | 8,5 mm | 8,5 mm | 8,5 mm | 8,5 mm | 8,5 mm |
| Pz/Box | 3 | 4 | 26 | 6 | 6 |
| m²/Box | 1,08 | 0,96 | 0,82 | - | - |
| kg/m² | 19,21 | 19,18 | 20,12 | - | - |
| Box/Pallet | 36 | 60 | 42 | - | - |
| m²/Pallet | 38,88 | 57,60 | 34,44 | - | - |
| Kg/Pallet | 747 | 1104,6 | 693 | - | - |

Cognac 24X150 - 9.5"x59"

| | | | | | | | | | | |
|---|---|---|---|---|---|---|---|---|---|---|
|  |  |  |  |  |  |  |  |  |  |  |
| NATURAL <0,15% OILED < 0,1% | NATURAL A-HA-LA OILED A-LA-HB | RESISTANT | NATURAL >50 N/mm ² OILED >48 N/mm ² | NATURAL 7 OILED 5 | NATURAL 5 OILED 4 | NATURAL R10 | NATURAL B | NATURAL >0,42 | V2 | SP 8,5 |



FLOOR FEELWOOD BLONDE 24X150 _9.5X59"

All technical features stated in leaflets, in master brochure and in merchandising of the products BOTTEGA® are meant to be an indication of an average of figures recorded within a span (determined by international law) in several production runs, therefore a slight discrepancy in quality figures of a certain batch in relation to these figures cannot be considered a production failure. BOTTEGA® products comply with the current regulations. Any possible information about weights, measures, dimensions, colors, shades and other data contained throughout the illustrative material is indicative and not binding. To enhance the effect of shaded materials it is recommended to lay the material by alternately taking it from different boxes. When laying rectified products it is advisable to use a self-levelling floor plaster with joints of not less than 2^{mm}. ITALCER S.p.A. will not be responsible for defects resulting from the incorrect laying of material. ITALCER S.p.A. reserves the right to modify the technical information reported. The colours and aesthetic features of the products are approximate, as it is not possible to reproduce them faithfully on paper.

BOTTEGA®

ITALCER SpA Italia +39 0522 625111 www.bottegotiles.com - info@bottegotiles.com